

QMI MATERIAL SAFETY DATA SHEET**QMI Dri Fuel -- #GL1880**

Revision Date: 08/29/2011

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

QMI Telephone: 863-665-3338
3606 Craftsman Blvd Emergency telephone: 800-255-3924
Lakeland, FL 33083
USA

Product name: QMI Dri Fuel
Product code: GL1880

2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance: liquid,, Colorless

WARNING! FLAMMABLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects**Routes of exposure**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury. Exposure causes severe irritation of the gastrointestinal tract.

QMI**MATERIAL SAFETY DATA SHEET****QMI Dri Fuel -- #GL1880**

Revision Date: 05/18/2009

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., Skin, lung (for example, asthma-like conditions), kidney

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), lowered blood pressure, mild, temporary changes in the liver, effects on heart rate, respiratory depression (slowing of the breathing rate), lack of coordination, confusion, lung edema (fluid buildup in the lung tissue), kidney damage, coma

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Breathing isopropanol vapors has caused damage to the lining of the middle ear in experimental animals. The relevance of this finding to humans is uncertain., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:., mild, reversible liver effects

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

QMI

MATERIAL SAFETY DATA SHEET

QMI Dri Fuel -- #GL1880

Revision Date: 05/18/2009

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Concentration</u>
ISOPROPANOL	67-63-0	<=100%

4. FIRST AID MEASURES**Eyes**

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver toxicity in experimental animals.

Treatment: No information available.

QMI**MATERIAL SAFETY DATA SHEET****QMI Dri Fuel -- #GL1880**

Revision Date: 05/18/2009

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**Dry chemical, Alcohol-resistant foam, Carbon dioxide (CO₂)**Hazardous combustion products**

May form: carbon dioxide and carbon monoxide

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Flammability Class for Flammable Liquids

Flammable Liquid Class IB Flammable Liquid Class IB

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Environmental precautions

No data

Methods for cleaning up

Per good environmental management practices, prevent run-off to sewers, streams and other bodies of water. Stop spill at the source. Cover sewer grates and dike the spill. Absorb spilled material on to absorbents. Shovel materials into container. Close container tightly and dispose of properly. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

QMI**MATERIAL SAFETY DATA SHEET****QMI Dri Fuel -- #GL1880**

Revision Date: 05/18/2009

7. HANDLING AND STORAGE**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Small quantities of peroxides may form on prolonged storage. Exposure to light and/or air significantly increases the rate of peroxide formation. If evaporated to a residue, the mixture of peroxides and isopropanol may explode when exposed to heat or shock.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines****ISOPROPANOL****67-63-0**

NIOSH (REL):	Recommended exposure limit	400 ppm
NIOSH (REL):	Recommended exposure limit	980 mg/m ³
NIOSH	Short term exposure limit	500 ppm
NIOSH	Short term exposure limit	1,225 mg/m ³
OSHA Z1	Permissible exposure limit	400 ppm
OSHA Z1	Permissible exposure limit	980 mg/m ³
ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	400 ppm

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

QMI**MATERIAL SAFETY DATA SHEET****QMI Dri Fuel -- #GL1880**

Revision Date: 05/18/2009

Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES
--

Physical state	Liquid
Form	Liquid
Colour	Colorless
Odour	Pleasant odor
Boiling point/boilingrange	82.50 °C / 180.5 °F@ 101.32 kPa
Melting point/range	-127.3 °F / -88.5 °C
pH	No data
Flash point	54 °F / 12 °C, Closed Cup
Evaporation rate	7.70 (Ethyl Ether)
Explosion limits	2.5 %(V) 12 %(V)
Vapour pressure	6.05 kPa @ 77 °F / 25 °C
Vapour density	2.1 (AIR=1)
Density	0.789 g/cm ³ @ 60 °F / 16 °C 6.65 lb/gal @ 60.1 °F / 15.6 °C
Solubility	Soluble in water
Partition coefficient: n-octanol/water	No data
Autoignition temperature	750 °F / 399 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

QMI

MATERIAL SAFETY DATA SHEET

QMI Dri Fuel -- #GL1880

Revision Date: 05/18/2009

Conditions to avoid

Avoid contact with:

Incompatible products

Avoid contact with:., acetaldehyde, Acids, aldehydes, alkalis, Amines, chlorinated hydrocarbons, Chlorine, ethylene oxide, halogens, isocyanates, Strong acids, strong oxidizing agents, Do not use with aluminum equipment at temperatures above 120 degrees F.

Hazardous decomposition products

May form:., carbon dioxide and carbon monoxide

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition No

data

11. TOXICOLOGICAL INFORMATION**Acute oral toxicity**

ISOPROPANOL

LD 50 Rat: 5,045 mg/kg

Acute inhalation toxicity

ISOPROPANOL

LC 50 Rat: 16000 ppm, 4 h

Acute dermal toxicity

ISOPROPANOL

LD 50 Rabbit: 5,030 - 7,900 mg/kg

12. ECOLOGICAL INFORMATION**Aquatic toxicity****Acute and Prolonged Toxicity to Fish:** No data**Acute Toxicity to Aquatic Invertebrates:** No data**Environmental fate and pathways:** No data

QMI**MATERIAL SAFETY DATA SHEET****QMI Dri Fuel -- #GL1880**

Revision Date: 05/18/2009

13. DISPOSAL CONSIDERATIONS**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION**IMDG:**

UN1219, ISOPROPANOL 3, II

IATA_P:

UN1219, Isopropanol 3, II

IATA_C:

UN1219, Isopropanol 3, II

CFR_ROAD:

UN1219, Isopropanol 3, II

CFR_RAIL:

UN1219, Isopropanol 3, II

CFR_INWTR:

UN1219, Isopropanol 3, II

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

SARA Hazard Classification Fire Hazard

Acute Health Hazard

SARA 313 Component(s)

	Health	Flammability	Reactivity	Other
HMIS	1	3	0	
NFPA	1	3	0	

QMI

MATERIAL SAFETY DATA SHEET

QMI Dri Fuel -- #GL1880

Revision Date: 05/18/2009

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.