

QMI GEAR OIL SAE 75W-90

Description

A vehicle's differential is comprised of two primary gears (the ring and pinion) and other secondary gears (spider, axle), plus various bearings and seals. These gears drive each other by "meshing" together. When two teeth mesh, the entire weight, power and torque of the vehicle applies directly to those two teeth. Since this load bearing surface area is very small, the demand on lubrication is extremely high. Gear oils must perform under these extreme pressure situations while maintaining viscosity in all temperature ranges, perform in both high and low speed environments, remove heat, lubricate bearings, resist moisture and protect against corrosion!

QMI Gear Oil SAE 75W-90 meets or exceeds OEM requirements for non-synthetic gear oils.



Applications

Differentials and manual transmissions using non-synthetic SAE 75W-90 gear oil.

Features & Benefits

Features	Benefits
Compatible	Meets or exceeds OE requirements for non-synthetic differential fluids
Wear reduction	Increased differential life
Improved performance	Less friction related power loss
Reduced heat	Diminishes differential oil's greatest enemy
Smoother operation	Helps mechanisms operate freely

SAE Gear Oil Viscosity Grade: 75W-90

API Service Classification: GL-5

Packaging

<u>Part#</u>	<u>Container Size</u>	<u>Package</u>
GGN90	55 ounces/1.6 liter	6 per case
GGN90D	55 Gallons	Unit